



MICRO TOPPING

SINGLE COMPONENT CEMENTICIOUS OVERLAY



MICRO TOPPING IS A CEMENT BASED, POLYMER MODIFIED DECORATIVE CONCRETE TOPPING MATERIAL. SINGLE COMPONENT MICRO TOPPING IS A THINLY APPLIED TOPPING THAT CLOSELY RESEMBLES THE LOOK OF NATURAL CONCRETE.

PRODUCT HIGHLIGHTS

- High bond, flexural and compressive strength. Consistent and evenly textured finish.
- Can be integrally colored with EZChem EZ Color Paks.
- Can be stained with EZChem Enviro Stain or Earthtone Stain for a wide array of decorative finishes.
- Can be sealed with EZChem Clear Acrylic Sealer or Colored Acrylic Sealer for a consistently colored and durable surface.
- Packaged in 40lb bags

USES

Single Component Micro Topping is used to re-surface concrete that is worn, pitted or spalled. Single Component Micro Topping can be used interior or exterior over existing structurally sound horizontal concrete surfaces including decks, patios, sidewalks, driveways, casinos, hotels, floors, or most other residential or commercial concrete surfaces. May also be used on vertical concrete surfaces. Single Component Micro Topping is compatible with EZChem EZ Pak Colorants for integral pigmentation and with EZChem Acid Stains and Enviro Water Based Stains for producing unique color effects.

QUICK LOOK:

Type :
Toxicity:
VOC's: Zero
Flammability: Non-flammable
Composition:
Odor: N/A
Coverage: 30-60ft² (2.78-5.57m²) per bag when applied @ 1/8-1/16inch (3.17-1.58mm) thickness
**Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

Application Temperature:
Cured:



FOR MORE INFORMATION,
PLEASE SEE SDS.



MICRO TOPPING

SURFACE PREPERATION:

The surface must be clean and free of any dirt or debris and properly prepared. Just prior to applying Micro Topping, the substrate must be primed with Bond It primer. Do not allow Bond It primer to dry completely. Micro Topping must be applied over wet Bond It.

HOW TO USE:

One 40 pound bag of Micro Topping will require approximately 7 1/2 to 8 quarts of water. For best results use a 1/2 inch drill with a Jiffy type mixing paddle. Add the measured water to a clean 5 - gallon pail. Add one EZ Color Pak pigment pack to your measured water and mix in. With the mixer running, slowly add the Micro Topping powder, mixing until a lump free consistency is obtained. Allow the mixed material to set, or slake for approximately 5 minutes and then re-mix prior to placement. Mix only the amount of material that can be placed within 30 minutes of mixing. Keep bagged material and mixed material out of direct sunlight for added work time. Use cold water when mixing for added working time. In cooler conditions, use warm water when mixing. Consult product technical data sheet for surface preparation and installation.

PRECAUTIONARY STATEMENT:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to approved waste disposal site.

FIRST AID:

INHALATION: Move to fresh air to avoid nuisance symptoms.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Rinse well. If irritation develops Get Medical Help.

EYE CONTACT: Rinse thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

INGESTION: Rinse mouth with water. Drink 2 glasses of water to dilute. Do not induce vomiting. Get Immediate Medical Help. Never give anything by mouth to an unconscious person.

IN CASE OF FIRE:

This product is not flammable.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053