



# SUPER SOLVE

## SPECIALTY SOLVENT FOR POWDERED POLISHING DYE



***SUPER SOLVE IS A SOLVENT CARRIER DESIGNED TO BE USED WITH EZCHEM POWDERED POLISHING DYES.***

### PRODUCT HIGHLIGHTS

- Leaves no or very little residual dye on surface
- **Coverage:** Super Solve doubles the coverage rate of dyes to 100sq.ft. per gallon
- Lower evaporation rate
- **Higher Grit Application:** Super Solve allows dyes to be applied at higher grit levels such as 800 or 1,500 grit for color enhancement or refurbishing
- Indefinite shelf life
- Available in 1 gallon, 5 gallon, and 55 gallon drums

### PERFECT FOR

- Concrete floors
- Powdered polishing dyes

### QUICK LOOK:

Type: Solvent  
VOC's: <249g/L  
Toxicity: Harmful if swallowed  
Flammability: Flammable  
Composition:  
Color: Clear  
Odor: Solvent



FOR MORE INFORMATION,  
PLEASE SEE SDS.

Manufactured In The USA By



\*Product warranty for one year from date of manufacture

For more information on EZChem and all products manufactured by EZChem please visit our website: [www.ezchemusa.com](http://www.ezchemusa.com)



# SUPER SOLVE

## **HOW TO USE:**

Super Solve is intended to be mixed with EZChem Powdered Polishing Dyes or Liquid Polishing Dyes. Mix one gallon o Super Solve to each container of Polishing Dye.

## **PRECAUTIONARY STATEMENT:**

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion- proof electrical, ventilating, lighting and all material-handling equipment. Use only non- sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapor.

## **DANGER:**

Danger! Highly flammable. Flash point at 64.4 degrees F/ 18 degrees C. Vapors may cause flash fire or ignite explosively. Vapors may travel long distances to other areas and rooms away from work site. Keep away from heat, sparks, flame and all other sources of ignition. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and all other sources of emission anywhere in the structure, dwelling or building during use and wait until vapors are gone from the work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources. Use only with adequate ventilation to prevent buildup of vapors. If using indoors open all windows and doors and maintain the cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye watering - STOP - ventilation is inadequate.

## **FIRST AID:**

IF INGESTED: Do not induce vomiting. Get Medical Help.

IF IN EYES: Flush thoroughly with water for 15 minutes, lifting both eyelids. If irritation continues, Get Medical Help.

IF ON SKIN: Rinse off thoroughly with soap and water. Wash contaminated clothing before reuse.

INHALATION: Remove to fresh air. Give resuscitation and oxygen if required. Get Medical Attention.

## **IN CASE OF FIRE:**

Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam. Do not use water jet.

## **STORAGE:**

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well- ventilated area, away from incompatible materials and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Store above 40°F.

## **FOR EMERGENCY HELP**

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053