



AQUA CLEAR COAT

WATER BASED CLEAR ACRYLIC FLOOR SEALER



AQUA CLEAR COAT IS A UNIQUE NEW WATER BASED ACRYLIC COATING THAT WILL ENHANCE THE COLOR AND BRILLIANCE OF AN ACID STAINED CONCRETE FLOOR EQUAL TO THE TYPICAL SOLVENT BASED SEALER WITHOUT THE SMELL OR HAZARD.

PRODUCT HIGHLIGHTS

- **No Hazardous Fumes:** Aqua Clear Coat does not emit flammable or toxic fumes, and can be used where normal ventilation is available.
- **Nonflammable:** Aqua Clear Coat itself is not flammable or combustible. The risk of fire is essentially eliminated.
- **Low Toxicity:** Once dry and cured overnight, Aqua Clear Coat is non-toxic, colorless and odorless.
- **Scuff Resistant and Water Resistant:** This tough coating is non-slip and non-blushing when wet.
- **Available in 1 gallon and 5 gallon**

Aqua Clear Coat is an ultra low VOC coating with no aromatic or chlorinated solvents. It meets all California VOC standards.

Indoors, protect it with EZ Glo Polish: After the coating has dried for 48 hours, it can be top coated with the water based acrylic polish EZ Glo, to produce a renewable wear surface. Therefore, with normal, easy maintenance Aqua Clear Coat will never wear out or need replacing.

PERFECT FOR

- Stained or Dyed Concrete Floors
- Walls
- Counter tops

Aqua Clear Coat is used as a sealer and a beautifier for any interior areas where flammable solvent based sealers are too hazardous to use.

QUICK LOOK:

Type: Stable water based dispersed coating

Toxicity: Low - Harmful if swallowed

VOC's: Less than 100gm per L

Flammability: Non-flammable

Composition: Special proprietary resins in a solvent

Solids: 31% (+/-)

Color: Dry coat is colorless

Odor: Mild

Coverage: 800-1000 sq.ft.

**Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,
PLEASE SEE SDS.





AQUA CLEAR COAT

HOW TO USE:

Before coating, the floor must be clean and free of oil, dirt, and chemical residue. Acid stained floors must be rinsed thoroughly to be free of any residues, and dry before sealing.

To the clean dry floor apply Aqua Clear Coat by roller only. Apply three thin coats at the rate of 800 – 1000 sq.ft. per gallon for each coat.

Allow each coat to dry for one hour and apply the next coat. Allow to dry for 24 hours before allowing traffic.

Do not over apply. Make sure concrete is cured and totally dry before applying. Do not allow to puddle. Any lines, high areas or marks created by roller need to be rolled back out to level out while still wet.

CLEAN UP:

Wash brushes and equipment with warm water and soap. Rinse clean.

PRECAUTIONARY STATEMENT:

Do not handle until all safety precautions have been read and understood. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Dispose of contents/container according to local, state and federal regulations.

FIRST AID:

EYES: Flush with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

INHALATION: Remove to fresh air immediately. If breathing difficulties continue, Get Medical Help.

INGESTION: Do not induce vomiting. Rinse mouth with water, and drink two glasses of water. Get Immediate Medical Help.

SKIN: Wash with soap and water. Remove contaminated clothing and launder before reuse.

IN CASE OF FIRE:

This product is not flammable.

FOR PROFESSIONAL USE ONLY

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053

