



BUBBLE GUM LIQUID RELEASE

HOW TO USE:

Apply Bubblegum LR with a pump up type sprayer. Apply to surfaces at the rate of 200 ft² per gallon for concrete, and 175 ft² per gallon for polymer overlays.

1. Spray the tools. Usually one coat is sufficient.
2. Spray the surface to be stamped. Only cover an area that can be stamped in approximately 20 minutes, or a second application may be required.
3. Allow the floor to stand open for several hours. The Bubblegum LR will evaporate. Never trowel Liquid Release into the fresh concrete.
* Bubblegum LR contains no hazardous aromatic solvents, and with a flash point greater than 142°F (61°C), it poses a far lower safety hazard than common liquid release agents and without the mess of powders. This is particularly important with interior applications.

PRECAUTIONARY STATEMENT:

Keep away from away from open/hot surface. No smoking. Wear protective gloves/eye protection/face protection. Store locked up in a well-ventilated place. Keep cool. Dispose of contents/container according to local, state and federal regulations.

FIRST AID:

IF INGESTED: Do not induce vomiting. Get Immediate Medical Help. Never give any liquids by mouth to an unconscious person.

IF IN EYES: Flush thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

IF INHALED: Remove to fresh air.

IF ON SKIN: Rinse off thoroughly with water then soap and water. Wash contaminated clothing before reuse.

IN CASE OF FIRE:

This product is combustible. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.

FOR PROFESSIONAL USE ONLY

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053

