



# VERTICAL STAMP MIX

## SINGLE COMPONENT CEMENTICIOUS OVERLAY



**VERTICAL STAMP MIX IS A READY TO USE, ONE COMPONENT OVERLAY SYSTEM THAT BONDS TO ALL CLEAN CONCRETE SURFACES TO PRODUCE A ROCK HARD WEATHER PROOF SURFACE. IT CAN BE TROWELED OR STAMPED AND SEALED FOR A BEAUTIFUL, LONG LIFE FLOOR.**

### PRODUCT HIGHLIGHTS

- One component mix. No extra additives. Just add water, mix and apply. Saves time and money.
- Ease of application. When applied with the Hopper Spray Gun, the application is fast and easy.
- Resurfaces old and worn concrete, restoring a like new appearance that lasts for years.
- Rock hard surface: Vertical Stamp Mix sets to a superior, rock hard surface that resists water penetration and re-wetting. This means beauty that lasts.
- Stains fast and easy: Although the surface is rock hard, it will take acid stains or water based stains with equal ease.
- Properly sealed this is a low maintenance surface that is easy to keep clean.
- Interior surfaces coated with EZ GLO™ acrylic polish over the initial seal coat can be maintained for years and never need resealing.
- Packaged in 40lb bags

### USES

Vertical Stamp Mix is used to restore and beautify commercial and residential areas such as patios, walk ways, pool decks, driveways, and interior basement rooms, bath rooms and kitchens. It re-surfaces and restores all concrete surfaces with one simple application.

### QUICK LOOK:

**Type :** Single component cementacious overlay system

**Toxicity:** Low. Alkaline mixture. Harmful if swallowed.

**VOC's:** Zero

**Flammability:** Non-flammable

**Composition:** Portlant cement, sand and proprietary additives.

**Odor:** N/A

**Coverage:** 60ft<sup>2</sup>

*\*Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

**Application Temperature:**

**Cured:**

FOR MORE INFORMATION,  
PLEASE SEE SDS.





# VERTICAL STAMP MIX

## HOW TO USE:

An initial aggressive scratch coat of Bond Coat should be applied and allowed to dry before applying Vertical Stamp Mix. Temperature should be 40 degrees or above for a period of 48 hours.

To Mix the 40lbs Bag: Place 5.5-6 quarts of clean, cool water in a separate bucket. Add a EZ-Color Pak, if desired, and mix for five minutes. Add half of the bucket of Vertical Stamp Mix to the bucket of water and mix until product is evenly dispersed. Add the rest of the product and mix for three to five minutes. Let the product set up for five minutes and re-mix thoroughly. You may need to add small amounts of water to make the mix workable.

(Caution: Too much water can reduce the strength of concrete and in some cases cause cracking.)

The scratch coat should be wetted with Acrylo Bond immediately before applying Vertical Stamp Mix. Apply Vertical Stamp Mix to the scratch coat using a trowel. When a finger is able to press lightly into the product without removing material, a texture can be embossed into the surface. Use Bubblegum Liquid Release on all stamps before you start the stamping processes.

## PRECAUTIONARY STATEMENT:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to approved waste disposal site.

## FIRST AID:

INHALATION: Move to fresh air to avoid nuisance symptoms.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Rinse well. If irritation develops Get Medical Help.

EYE CONTACT: Rinse thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

INGESTION: Rinse mouth with water. Drink 2 glasses of water to dilute. Do not induce vomiting. Get Immediate Medical Help. Never give anything by mouth to an unconscious person.

## IN CASE OF FIRE:

This product is not flammable.

## FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053